

QINGDAO KELUCK TYRE Co., Ltd.

TUBELESS STEEL WHEEL RIM-----19.5 SERIES

PHOTO

| Wheel size | Bolt Hole | | | P.C.D (mm) | Center Bore DIA (mm) | DISC Thick (mm) | Offset (mm) | TEC.TYPE | QTY/ 20GP | |
|------------------|-------------------|----|-----------------|---------------|----------------------------|-----------------------|----------------|---|--------------|---|
| | Hole DIA(mm) | NO | Nut Type | | | | | | | |
| 19.5×6.00 | | | | | | | | | | |
| 19.5×6.00 | 29/32 | 5 | 1*45° | 203.5 | 146 | | 115 | 205/75R19.5 215/75R19.5 225/75R19.5 8R19.5 8.5R19.5 | 360 |  |
| 19.5×6.00 | 32.5 | 5 | SR22 | 208 | 150 | | 120 | | | |
| 19.5×6.00 | 20.5/21.5 | 6 | SR16/SR18/1*45° | 190 | 140 | | 115 | | | |
| 19.5×6.00 | 20.5/21.5 | 6 | 1*45° | 205 | 161 | | 125 | | | |
| 19.5×6.00 | 32.5 | 6 | SR22 | 222.25 | 164 | | 135 | | | |
| 19.5×6.00 | 21.5 | 6 | SR16 | 245 | 202 | | 135 | | | |
| 19.5×6.00 | 26/21.5/24.5/25.4 | 8 | SR16/SR18/1*45° | 275 | 221 | | 134 | | | |
| 19.5×6.00 | 26 | 10 | 1*45° | 225 | 176 | | 133 | | | |
| 19.5×6.00 | 26/32 | 5 | SR16/SR18/1*45° | 205 | 161 | | 125 | | | |
| 19.5×6.75 | | | | | | | | | | |
| 19.5×6.75 | 32.5 | 6 | 1*45°/SR22 | 203.2 | 146 | | 115 | 95/60R19.5 205/60R19.5 7R19.5 | 360 |  |
| 19.5×6.75 | 32 | 8 | SR22 | 208 | 150 | | 120 | | | |
| 19.5×6.75 | 26/21.5/24.5/25.4 | 8 | 1*45°/SR22 | 190 | 140 | | 108 | | | |
| 19.5×6.75 | 21.5 | 8 | 1*45° | 205 | 161 | | 125 | | | |
| 19.5×6.75 | 26/21.5 | 10 | SR22 | 222.25 | 164 | | 135 | | | |
| 19.5×6.75 | 24.5 | 10 | SR16/1*45° | 245 | 202 | | 135 | | | |
| 19.5×6.75 | 21 | 10 | 1*45°/SR22/SR18 | 205 | 161 | | 125 | | | |
| 19.5×7.50 | | | | | | | | | | |
| 19.50×7.50 | 32.5/26 | 5 | 1*45°/SR22/SR18 | 205 | 164 | | 145 | 10R19.5 245/70R19.5 265/70R19.5 285/70R19.5 | 360 |  |
| 19.50×7.50 | 32.5 | 8 | SR22 | 275 | 214 | | 145 | | | |
| 19.50×7.50 | 26/21.5/24.5/25.4 | 8 | SR16/SR18/1*45° | 275 | 221 | | 135 | | | |
| 19.50×7.50 | 32.5 | 8 | SR22 | 285 | 221 | | 145 | | | |
| 19.50×7.50 | 26 | 10 | 1*45° | 285.75 | 220 | | 145 | | | |
| 19.50×7.50 | 26/21.5 | 10 | SR16/SR18/1*45° | 176 | 225 | | 135 | | | |

| | | | | | | | | | |
|------------------|-----------|----|------------|--------|-----|--|-------|---|-----|
| 19.50×7.50 | 20.5/21.5 | 6 | SR16/1*45° | 205 | 164 | | 145 | | |
| 19.5×8.25 | | | | | | | | | |
| 19.5×8.25 | 32.5 | 5 | SR22 | 205 | 161 | | 0 | 10R19.5 11R19.5 265/70R19.5 285/70R19.5 305/70R19.5 | 360 |
| 19.5×8.25 | 21.5 | 8 | SR16/1*45° | 275 | 221 | | 66 | | |
| 19.5×8.25 | 25.4/24.5 | 8 | SR18/1*45° | 275 | 221 | | 0 | | |
| 19.5×8.25 | 26 | 8 | SR18/1*45° | 275 | 221 | | 146 | | |
| 19.5×8.25 | 32.5 | 8 | SR22 | 285 | 221 | | 153.5 | | |
| 19.5×8.25 | 21 | 10 | SR16/1*45° | 225 | 176 | | 146.5 | | |
| 19.5×8.25 | 26 | 10 | SR18/1*45° | 225 | 176 | | 0 | | |
| 19.5×8.25 | 26 | 10 | 1*45° | 285.75 | 220 | | 146.5 | | |

| | | | | | | | | | |
|-------------------|-----------|----|------------|--------|-----|--|-----|------------------------|-----|
| 19.5×14.00 | | | | | | | | | |
| 19.5×14.00 | 21.5/24.5 | 8 | SR16/1*45° | 275 | 221 | | 0 | 18R19.5 445/65R19.5 | 280 |
| 19.5×14.00 | 25.4/26 | 8 | SR18/1*45° | 275 | 221 | | 120 | | |
| 19.5×14.00 | 26 | 10 | 1*45° | 285.75 | 220 | | 0 | | |
| 19.5×14.00 | 26 | 10 | 1*45° | 335 | 281 | | 0 | | |
| 19.5×14.00 | 27 | 10 | SR18 | 335 | 281 | | 120 | | |
| 19.5×14.00 | 20.5/21.5 | 6 | SR16/1*45° | 205 | 161 | | 0 | | |

TUBELESS STEEL WHEEL RIM-----22.5 SERIES

| Wheel size | Bolt Hole | | | P.C.D (mm) | Center Bore DIA (mm) | DISC Thick (mm) | Offset (mm) | TEC.TYPE | QTY/ 20GP |
|------------|--------------|----|----------|---------------|----------------------------|-----------------------|----------------|----------|--------------|
| | Hole DIA(mm) | NO | Nut Type | | | | | | |

| | | | | | | | | | |
|------------------|---------|----|-----------------|--------|-----|--|-----|---|-----|
| 22.5*6.00 | | | | | | | | | |
| 22.5×6.00 | 32.5 | 6 | SR22 | 222.25 | 164 | | 135 | 205/75R22.5 215/75R22.5 225/75R22.5 8R22.5 8.5R22.5 | 360 |
| 22.5×6.00 | 20.5 | 6 | SR16/SR22/1*45° | 190 | 140 | | 135 | | |
| 22.5×6.00 | 21.5 | 6 | SR16 | 245 | 202 | | 138 | | |
| 22.5×6.00 | 32.5 | 8 | SR22 | 275 | 214 | | 140 | | |
| 22.5×6.00 | 32.5 | 8 | SR22 | 285 | 221 | | 135 | | |
| 22.5×6.00 | 26/21.5 | 10 | SR16/SR18/1*45° | 225 | 176 | | 130 | | |

| | | | | | | | | | |
|------------------|----|---|------|-----|-----|--|-----|--------|--|
| 22.5×6.75 | | | | | | | | | |
| 22.5×6.75 | 32 | 8 | SR22 | 275 | 214 | | 152 | 8R22.5 | |
| 22.5×6.75 | 32 | 8 | SR22 | 285 | 221 | | 140 | | |



| | | | | | | | | | |
|-------------------|-------------------|----|-----------------|--------|-----|--|-------|--|-----|
| 22.5×6.75 | 26/21.5/24.5/25.4 | 8 | SR16/SR18/1*45° | 275 | 221 | | 140 | SR22.5 9R22.5 10R22.5 22.5/70R22.5 | 360 |
| 22.5×6.75 | 32 | 10 | SR22 | 285.75 | 222 | | 140.5 | | |
| 22.5×6.75 | 26 | 10 | 1*45 | 335 | 281 | | 142 | | |
| 22.5×6.75 | 27 | 10 | SR18 | 335 | 281 | | 142 | | |
| 22.5×7.50 | | | | | | | | | |
| 22.5×7.50 | 32 | 8 | SR22 | 275 | 214 | | 152 | 10R22.5 11R22.5 255/70R22.5 265/70R22.5 275/70R 22.5 275/80R 22.5 | 320 |
| 22.5×7.50 | 32 | 8 | SR22 | 285 | 221 | | 165 | | |
| 22.5×7.50 | 26/21.5/24.5/25.4 | 8 | SR16/SR18/1*45° | 275 | 221 | | 158 | | |
| 22.5×7.50 | 32 | 10 | SR22 | 285.75 | 222 | | 165 | | |
| 22.5×7.50 | 26 | 10 | 1*45 | 335 | 281 | | 152 | | |
| 22.5×7.50 | 27 | 10 | SR18 | 335 | 281 | | 152 | | |
| 22.5×8.25 | | | | | | | | | |
| 22.5×8.25 | 32 | 8 | SR22 | 275 | 214 | | 169 | 11R22.5 255/70R22.5 275/70R22.5 275/80R22.5 285/60R 22.5 295/80R 22.5 305/70R 22.5 | 280 |
| 22.5×8.25 | 32 | 8 | SR22 | 285 | 221 | | 165 | | |
| 22.5×8.25 | 26 | 8 | 1*45 | 275 | 221 | | 165 | | |
| 22.5×8.25 | 26 | 10 | 1*45 | 285.75 | 220 | | 165 | | |
| 22.5×8.25 | 32 | 10 | SR22 | 285.75 | 222 | | 169 | | |
| 22.5×8.25 | 27 | 10 | SR18 | 335 | 281 | | 169 | | |
| 22.5×8.25 | 26 | 10 | 1*45 | 335 | 281 | | 169 | | |
| 22.5×9.00 | | | | | | | | | |
| 22.5×9.00 | 32 | 8 | SR22 | 275 | 214 | | 175 | 12/13R22.5 215/75R 22.5 285/60R22.5 295/60R22.5 295/80R22.5 305/60R22.5 305/70R22.5 315/60/70R22.5 315/75/80R 22.5 | 280 |
| 22.5×9.00 | 32 | 8 | SR22 | 285 | 221 | | 175 | | |
| 22.5×9.00 | 26 | 8 | 1*45 | 275 | 221 | | 175 | | |
| 22.5×9.00 | 26 | 10 | 1*45 | 285.75 | 220 | | 175 | | |
| 22.5×9.00 | 32 | 10 | SR22 | 285.75 | 222 | | 175 | | |
| 22.5×9.00 | 27 | 10 | SR18 | 335 | 281 | | 175 | | |
| 22.5×9.00 | 26 | 10 | 1*45 | 335 | 281 | | 175 | | |
| 22.5×11.75 | | | | | | | | | |
| 22.5×11.75 | 21.5/24.5/25.4 | 8 | SR16/1*45° | 275 | 221 | | 0 | 385/65R22.5 15R22.5 | 240 |
| 22.5×11.75 | 26 | 8 | SR18/1*45° | 275 | 221 | | 120 | | |
| 22.5×11.75 | 26 | 10 | 1*45 | 335 | 281 | | 120 | | |




| | | | | | | | | | |
|-------------------|------|----|------------|--------|-----|--|-----|---|-----|
| 22.5×11.75 | 27 | 10 | SR18 | 335 | 281 | | 0 | | |
| 22.5×14.00 | | | | | | | | | |
| 22.5×14.00 | 21.5 | 8 | SR16/1*45° | 275 | 221 | | 0 | 18R22.5 425/65 R22.5 445/65R22.5 445/75R22.5 | 200 |
| 22.5×14.00 | 26 | 8 | SR18/1*45° | 275 | 221 | | 0 | | |
| 22.5×14.00 | 32 | 10 | SR22 | 285.75 | 222 | | 60 | | |
| 22.5×14.00 | 26 | 10 | 1*45° | 285.75 | 220 | | 75 | | |
| 22.5×14.00 | 26 | 10 | 1*45° | 335 | 281 | | 120 | | |
| 22.5×14.00 | 27 | 10 | SR18 | 335 | 281 | | 0 | | |
| 22.5×16.00 | | | | | | | | | |
| 22.5×16.00 | 21.5 | 8 | SR16/1*45° | 275 | 221 | | 0 | 550/65R22.5 | 200 |
| 22.5×16.00 | 26 | 8 | SR18/1*45° | 275 | 221 | | 0 | | |
| 22.5×16.00 | 32 | 10 | SR22 | 285.75 | 222 | | 60 | | |
| 22.5×16.00 | 26 | 10 | 1*45° | 285.75 | 220 | | 75 | | |
| 22.5×16.00 | 26 | 10 | 1*45° | 335 | 281 | | 120 | | |
| 22.5×16.00 | 27 | 10 | SR18 | 335 | 281 | | 0 | | |




TUBELESS STEEL WHEEL RIM-----17.5 SERIES

| Wheel size | Bolt Hole | | | P.C.D (mm) | Center Bore DIA (mm) | DISC Thick (mm) | Offset (mm) | TEC.TYPE | QTY/20GP |
|-------------------|--------------|----|-----------------|------------|----------------------|-----------------|-------------|-------------------------------------|----------|
| | Hole DIA(mm) | NO | Nut Type | | | | | | |
| 17.50×5.25 | | | | | | | | | |
| 17.50×5.25 | 29/32 | 5 | 1*45°/SR22 | 203.2 | 146 | | 115 | 95/60R17.5 205/60R17.5 7R17.5 | 450 |
| 17.50×5.25 | 32.5 | 5 | SR22 | 208 | 150 | | 120 | | |
| 17.50×5.25 | 20.5/21 | 6 | 1*45°/SR22 | 190 | 140 | | 108 | | |
| 17.50×5.25 | 20.5/21 | 6 | 1*45° | 205 | 161 | | 125 | | |
| 17.50×5.25 | 32.5 | 6 | SR22 | 222.25 | 164 | | 135 | | |
| 17.50×5.25 | 21.5 | 6 | SR16/1*45° | 245 | 202 | | 135 | | |
| 17.50×5.25 | 26/32 | 5 | 1*45°/SR22/SR18 | 205 | 161 | | 125 | | |
| 17.50×6.00 | | | | | | | | | |
| 17.50×6.00 | 29/32 | 5 | 1*45°/SR22 | 203.2 | 146 | | 115 | 205/75R17.5 | |
| 17.50×6.00 | 32.5 | 5 | SR22 | 208 | 150 | | 120 | | |
| 17.50×6.00 | 20.5/21.5 | 6 | SR16/SR22/1*45° | 190 | 140 | | 115 | | |




| | | | | | | | | | | |
|------------|-------------------|----|-----------------|--------|-----|--|-----|---|-----|--|
| 17.50×6.00 | 20.5/21.5 | 6 | 1*45° | 205 | 161 | | 125 | 205/75R17.5 215/75R17.5 225R/7517.5 8R17.5 8.5R17.5 | 450 |  |
| 17.50×6.00 | 32.5 | 6 | SR22 | 222.25 | 164 | | 135 | | | |
| 17.50×6.00 | 21.5 | 6 | SR16/1*45° | 245 | 202 | | 135 | | | |
| 17.50×6.00 | 26/21.5/25.4/24.5 | 8 | 1*45°/SR18/SR16 | 275 | 221 | | 134 | | | |
| 17.50×6.00 | 26/21.5 | 10 | 1*45°/SR18/SR16 | 225 | 176 | | 133 | | | |
| 17.50×6.00 | 26/32 | 5 | SR18/SR22/1*45° | 205 | 161 | | 125 | | | |

17.5×6.75

| | | | | | | | | | | |
|------------|-------------------|----|-----------------|--------|-----|--|-----|--------------------------------------|-----|---|
| 17.50×6.75 | 29/32 | 5 | 1*45°/SR22 | 203.2 | 146 | | 115 | 225/75R17.5 235/75R17.5 9R17.5 | 450 |  |
| 17.50×6.75 | 32.5 | 5 | SR22 | 208 | 150 | | 120 | | | |
| 17.50×6.75 | 20.5/21.5 | 6 | SR16/SR22/1*45° | 190 | 140 | | 115 | | | |
| 17.50×6.75 | 20.5/21.5 | 6 | 1*45° | 205 | 161 | | 125 | | | |
| 17.50×6.75 | 32.5 | 6 | SR22 | 222.25 | 164 | | 135 | | | |
| 17.50×6.75 | 21.5 | 6 | SR16 | 245 | 202 | | 135 | | | |
| 17.50×6.75 | 26/21.5/24.5/25.4 | 8 | SR16/SR18/1*45° | 275 | 221 | | 134 | | | |
| 17.50×6.75 | 26/21.5 | 10 | SR16/SR18/1*45° | 225 | 176 | | 133 | | | |
| 17.50×6.75 | 26/32 | 5 | SR16/SR22/1*45° | 205 | 161 | | 125 | | | |

TUBELESS STEEL WHEEL RIM-----24.5 SERIES

| Wheel size | Bolt Hole | | | P.C.D (mm) | Center Bore DIA (mm) | DISC Thick (mm) | Offset (mm) | TEC.TYPE | QTY/20GP | |
|------------|--------------|----|------------|------------|----------------------|-----------------|-------------|----------|----------|---|
| | Hole DIA(mm) | NO | Nut Type | | | | | | | |
| 24.5×8.25 | 32 | 8 | SR22 | 275 | 214 | | 169 | 11R24.5 | 208 |  |
| 24.5×8.25 | 32 | 8 | SR22 | 285 | 221 | | 165 | | | |
| 24.5×8.25 | 26 | 8 | 1*45°/SR18 | 275 | 221 | | 165 | | | |
| 24.5×8.25 | 26 | 10 | 1*45° | 285.75 | 220 | | 165 | | | |
| 24.5×8.25 | 32 | 10 | SR22 | 285.75 | 222 | | 169 | | | |
| 24.5×8.25 | 27 | 10 | SR18 | 335 | 281 | | 169 | | | |
| 24.5×8.25 | 26 | 10 | 1*45° | 335 | 281 | | 169 | | | |

TUBE STEEL WHEEL RIM-----24 SERIES

| Wheel size | Bolt Hole | | | P.C.D (mm) | Center Bore DIA (mm) | DISC Thick (mm) | Offset (mm) | TEC.TYPE | QTY/ 20GP |
|------------|--------------|----|-----------------|---------------|----------------------------|-----------------------|----------------|----------|--------------|
| | Hole DIA(mm) | NO | Nut Type | | | | | | |
| 8.50-24 | 27 | 10 | 1*45°/SR18/SR22 | 335 | 281 | | 180 | 12.00-24 | 208 |
| 8.50-24 | 32.5 | 8 | SR22 | 285 | 221 | | 180 | | |
| 8.50-24 | 32.5 | 10 | SR22 | 285.75 | 222 | | 180 | | |
| 8.50-24 | 26 | 10 | 1*45° | 285.75 | 220 | | 180 | | |
| 8.50-24 | 24.5 | 8 | 1*45° | 275 | 221 | | 175 | | |
| 8.50-24 | 21.5 | 8 | SR16 | 275 | 221 | | 175 | | |



TUBE STEEL WHEEL RIM-----20 SERIES

| Wheel size | Bolt Hole | | | P.C.D (mm) | Center Bore DIA (mm) | DISC Thick (mm) | Offset (mm) | TEC.TYPE | QTY/ 20GP |
|----------------|--------------|----|------------|---------------|----------------------------|-----------------------|----------------|----------|--------------|
| | Hole DIA(mm) | NO | Nut Type | | | | | | |
| 8.50-20 | | | | | | | | | |
| 8.50-20 | 26 | 10 | 1*45°/SR18 | 335 | 281 | | 180 | 12.00-20 | 320 |
| 8.50-20 | 32 | 8 | SR22 | 285 | 221 | | 180 | | |
| 8.50-20 | 26 | 10 | 1*45° | 285.75 | 220 | | 180 | | |
| 8.50-20 | 32 | 10 | SR22 | 285.75 | 222 | | 180 | | |
| 8.50-20 | 26 | 8 | 1*45° | 275 | 221 | | 180 | | |
| 7.50-20 | | | | | | | | | |
| 7.50-20 | 32 | 8 | SR22 | 285 | 221 | | 165 | 10.00-20 | 320 |
| 7.50-20 | 26 | 10 | 1*45° | 285.75 | 220 | | 165 | | |
| 7.50-20 | 26 | 10 | 1*45°/SR18 | 335 | 281 | | 165 | | |
| 7.50-20 | 32 | 10 | SR22 | 285.75 | 222 | | 165 | | |



7.00-20

| | | | | | | | | | |
|---------|----|----|-------|--------|-----|--|-----|---------|-----|
| 7.00-20 | 32 | 8 | SR22 | 275 | 214 | | 152 | 9.00-20 | 320 |
| 7.00-20 | 26 | 10 | 1×45° | 285.75 | 220 | | 152 | | |
| 7.00-20 | 32 | 10 | SR22 | 285.75 | 222 | | 152 | | |



TUBE STEEL WHEEL RIM-----16 SERIES

| Wheel size | Bolt Hole | | | P.C.D (mm) | Center Bore DIA (mm) | DISC Thick (mm) | Offset (mm) | TEC.TYPE | QTY/20GP |
|------------|--------------|----|----------|------------|----------------------|-----------------|-------------|----------|----------|
| | Hole DIA(mm) | NO | Nut Type | | | | | | |

6.5-16

| | | | | | | | | | |
|--------|------|----|-------|-------|-----|--|-------|---------|-----|
| 6.5-16 | 32 | 6 | 1×45° | 222.5 | 164 | | 123 | 8.25-16 | 780 |
| 6.5-16 | 32 | 6 | SR22 | 190 | 164 | | 127 | | |
| 6.5-16 | 24.5 | 8 | SR22 | 205 | 161 | | 125 | | |
| 6.5-16 | 20.5 | 6 | SR22 | 203.2 | 140 | | 125 | | |
| 6.5-16 | 26 | 10 | 1*45° | 225 | 176 | | 137.5 | | |
| 6.5-16 | 20.5 | 5 | SR22 | 208 | 140 | | 125 | | |



6.00G-16

| | | | | | | | | | |
|----------|------|---|-------|--------|-----|--|-----|-------------|-----|
| 6.00G-16 | 32 | 6 | SR22 | 222.25 | 164 | | 123 | 7.5/8.25-16 | 845 |
| 6.00G-16 | 20.5 | 6 | SR22 | 190 | 140 | | 125 | | |
| 6.00G-16 | 18 | 6 | 1×45° | 205 | 161 | | 125 | | |
| 6.00G-16 | 32 | 6 | SR22 | 203.2 | 140 | | 125 | | |
| 6.00G-16 | 32 | 5 | SR22 | 208 | 150 | | 115 | | |



5.5F-16

| | | | | | | | | | |
|---------|----|---|------|--------|-----|--|-----|--|--|
| 5.5F-16 | 32 | 6 | SR22 | 222.25 | 164 | | 104 | | |
|---------|----|---|------|--------|-----|--|-----|--|--|



| | | | | | | | |
|---------|------|---|------|--------|-----|--|-----|
| 5.5F-16 | 32.5 | 6 | SR22 | 222.25 | 164 | | 113 |
| 5.5F-16 | 20.5 | 6 | SR22 | 190 | 140 | | 115 |
| 5.5F-16 | 29 | 5 | SR22 | 203.2 | 146 | | 108 |
| 5.5F-16 | 32.5 | 5 | SR22 | 208 | 150 | | 115 |
| 5.5F-16 | 32.5 | 5 | SR22 | 203.2 | 146 | | 108 |
| 5.5F-16 | 32.5 | 5 | SR22 | 203.2 | 146 | | 112 |

7.00/7.5-16

845

